




- Hose** : MARINE FUEL HOSE, type FUHOSE__A
- Application** : Hoses are to be used for transportation of fuel, e.g. from tank to engine fuel filter, or as ventilation line on yachts and small craft
- Features** : Suitable for the following fluids:
- Diesel fuel (B7, max. 7% biodiesel)
 - Petrol fuel (E15, max. 15% =ethanol)
- Small bending radius
- Lining** : Fuel and oil resistant, black, nitrile rubber (NBR)
- Reinforcement** : Synthetic textile fabrics embedded between the layers.
- Cover** : Heat, weather, ozone, oil and abrasion resistant, black, neoprene rubber (CR).
- Temperature** : Suitable for use in the range - 25 to + 100° Celsius (- 13 to + 212° Fahrenheit)
(intermittent to + 115 °C, 239 ° F)
- Relevant Standards** : ISO 7840 A1 (2.5 min fire test, permeation rate of 100 g/m² or less per 24 h)
ISO 10088
: SAE J 1527 USCG Type A Class 1
- Classification** : Lloyds approval
- Certification** : RINA (RCD)

Code	I.D.		O.D	Working Pressure		Burst Pressure		Bending Radius		Weight	
	mm	inch	mm	bar	psi	bar	psi	mm	inch	kg/m	lbs/ft
FUHOSE06A	6	1/4	13	10	145	40	580	25	1	0.16	0.11
FUHOSE08A	8	5/16	16	10	145	40	580	30	1 3/16	0.24	0.16
FUHOSE10A	10	3/8	18	10	145	40	580	35	1 3/8	0.28	0.19
FUHOSE13A	13	1/2	22	10	145	40	580	50	2	0.39	0.26
FUHOSE16A	16	5/8	25	10	145	40	580	60	2 3/8	0.45	0.30
FUHOSE19A	19	3/4	28	10	145	40	580	80	3 1/8	0.52	0.35
FUHOSE25A	25	1	35	10	145	40	580	110	4 5/16	0.73	0.49

Identification:

   MARINE FUEL HOSE - I.D. 10 mm ISO7840 - A1 SAE J 1527 USCG TYPE A CLASS 1 - I.D. 3/8 "
<p>Black ribbon with white text over full length of hose 0.3 meter Mark, Hose type and dimension repeated every 0.3 meter</p>