

Hydraulic Tunnel Thruster

CT 300 HYD

Specifications

Code	317607
Model	CT 300 HYD
Max Thrust (kgf/lbs)	300 / 529
Hydraulic Power (k/w)	19,5
Propellers	Duo
Weight (kg)	24
A (mm)	240
B (mm)	240
C (mm)	240
D (mm)	300
E (mm)	9 to 10



Boat Type	Boat Length (feet/meter)	
Heavy Displacement High Windage & Cruising	48' - 63' / 14,6 - 19 m	ш
Medium Displacement Medium Windage & Fast Cruising	59' - 79' / 18 - 24 m	
Light Displacement Light Windage & Super Fast Cruising	67' - 93' / 20,4 - 28 m	





The twin propeller CT 300 HYD has a bronze drive leg. This model has a 300mm tunnel diameter, a thrust rating of up to 300 / 529 (kg/lbs) and integrates all the unique features of the range.

Unique Features:



Line shields



Case hardened spiro-conical gears



Branded hydraulic components



Water resistant



Unrivaled safety features

Control Panels:

Max Power's thruster control systems include a variety of advanced safety features.

- Childproof activation
- Automatic shutdown after 30 minutes of inactivity
- Visible and audible overheat warning
- Time delay switch bewteen port and starboard thrust
- Software protection against short circuits





